

Pax Pax Eos 100H

Cat. Part	1110-2
Number	
EAN 13	7391477111027
SE EL (SEG)	9302121
SE VVS (RSK)	6724023
NO EL (EFO)	4910501
NO VVS (NRF)	6553755
FI VVS (LVI)	7937301
DK EL (DB)	1784301
DK VVS (VVS)	353413120
FI EL (SNRO)	8510026



Pax Eos replace the air and retain heat.

- **Replaces the air and retains the heat**
- **Saves both heat and money**
- **Simple and attractive installation**

Ventilation unit with heat recovery. Equipped with preheater, humidity sensor and remote control. For fixed installation.

Functions

Humidistat, Airflow Sensor

Technical data

Installation type, wall, ceiling etc	Wall, Ceiling void, Ceiling
Free to air Max (m3/h)	90
Sound pressure level 3m dB(A)	19-35
Max watt(W)	25
Supply Voltage (12V-400V)	230V AC
Electrical Supply Phase	1-Phase
Insulation Class	II
Type of motor	EC
Protection (IP)	IP 24
Leakage (%)	5
Heater max. effect at OA -20 ° C (W)	375
Duct size nominal Ø (mm)	100
Unpackaged Product Width (mm)	720
Unpackaged Product Height (mm)	191
Unpackaged Product Depth (mm)	340
Material	Plastic
Plastic Material detail	ABS
Etim Code	EC011286

Description

Pax Eos with preheating provides an added advantage when it is cold outside. Before the cold air from outside enters the house, it is preheated to at least 18 ° C, so that it is close to ordinary room temperature right from the start. It is both nice and energy-saving. If you want Eos to automatically provide as economical operation as possible when it is cold outside, set Eco mode. If you want the automatics instead to give an even inflow of artificial red, comfortable air, switch to Comfort mode. For Scandinavian conditions Pax Eos is a solid building, equipped for Scandinavian conditions. Of course, it is tested and S-marked, double-insulated and IP24-rated. It has an EC motor, that is, a brushless DC motor that is incredibly

reliable. No condensation drain Eos does not need a condensation drain, because the intelligent control regulates the air flows so that condensation cannot occur. Filter replacement To ensure really good air quality and function, Eos has dual filters. They are easy to change themselves, which should be done once every six months - Eos tells himself when it's time. The standard filters are available for purchase via our retailers. Bad space in the bathroom? Do you have little room to mount Eos in the bathroom or laundry room? Then, on request, we can factory-assemble a pipe / hose connector for the exhaust air. In this way, Eos can be placed in, for example, an adjacent wardrobe.

Accessories



**Pax Eos
accessory
package**

Cat 8404-1



Silencer

Cat 8903-1



**Air supply vent
Ø100 steel**

Cat 2907-1




**Exhaust air
vent Ø100 steel**

Cat 2907-3



Filter

Cat 8400-5



**Pax Eos
external wall
kit**

Cat 8403-1



**Exhaust air kit
Eos**

Cat 8404-0