

CONTEGA SOLIDO IQ

Intelligent, full-surface adhesive plaster and window sealing tape for interior and exterior use



Technical data

| Substance | | |
|------------------------------------|--|--|
| Backing | PP backing fleece, PE copolymer special membrane | |
| Adhesive | modified waterproof SOLID adhesive | |
| Release film | one or two split silicone-coated PE sheet | |
| Attribute | Regulation | Value |
| Colour | | white, print: green |
| sd-value humidity variable | EN ISO 12572 | 0.4 - > 25 m |
| g-value humidity variable | | 2 - > 125 MN·s/g |
| Vapour permeance humidity variable | EN ISO 12572 | < 0.13 - 8 US perms |
| Outdoor exposure | | 3 months |
| Water column | EN ISO 811 | > 2.500 mm |
| Can be plastered over | | yes |
| Application temperature | | above -10 °C ; 14 °F |
| Temperature resistance | | permanent -40 °C to 90 °C ; -40 °F to 194 °F |
| Storage | | cool and dry |

Application

For interior airtight joints between windows or doors and vapour retarder and airtight layers.

Thanks to its intelligent, humidity-variable functional membrane, CONTEGA SOLIDO IQ is also suitable for exterior windproof and rainproof joints.

Width split release film

80 mm 20/60 mm
100 mm 20/40/40 mm
150 mm 20/70/60 mm
200 mm 20/100/80 mm

Advantages

- ✓ Reliable installation: the same tape for interior and exterior use thanks to its intelligent functional membrane
- ✓ Saves time: the joint is immediately windproof and resistant to driving rain, and it can be subjected to loading
- ✓ Reliable joints: waterproof SOLID adhesive has extremely strong adhesion on mineral substrates too
- ✓ Extra thin: for easy folding in corner areas
- ✓ Construction in adherence with standards: for airtight bonding in accordance with DIN 4108-7, SIA 180 and RT 2012
- ✓ Fleece side can be plastered over: defined transition between window joints and plaster
- ✓ Excellent values in the hazardous substance test, has been tested according to the ISO 16000 evaluation scheme

The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
Rheinalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de



Substrates

Clean subsurfaces before sticking.

Uneven mineral subsurfaces may need to be levelled with a smooth finish.

Adhesion to frozen surfaces is not possible. There must be no water-repellent substances (e.g. grease or silicone) on materials to be bonded.

The width of the adhesive tape that is to be plastered over should generally not exceed 60 mm (2 3/8") or 50% of the soffit area. Detailed recommendations can be obtained from the relevant plaster producer.

Subsurfaces must be sufficiently dry and stable.

Permanent adhesion is achieved on all pro clima interior and exterior membranes, other vapour retarder and airtight membranes (e.g. those made of PE, PA, PP and aluminium) as well as other roof and wall lining membranes (e.g. those made of PP and PET).

Adhesion can be carried out on planed and painted wood, hard plastics, hard wood-based panels (chipboard, OSB and plywood panels), metal (e.g. pipes, windows etc.) and on mineral subsurfaces such as concrete and masonry.

The best results in terms of structural stability are achieved on high-quality subsurfaces.

It is your responsibility to check the suitability of the subsurface; adhesion tests are recommended in certain cases.

Pretreatment with TESCON PRIMER is recommended in the case of subsurfaces with insufficient stability.


General conditions

The bonds should not be subjected to tensile strain.

Press firmly to secure the adhesive tapes in place. Ensure that there is sufficient resistance pressure. Driving rainproof and wind- or airtight seals can only be achieved if this connection tape is laid without folds or creases and are uninterrupted.


Ventilate continuously and systematically to prevent build-up of excessive humidity; use a dryer if necessary.

When plastering, please observe the recommendations of the plaster manufacturer for non-absorbent subsurfaces. A bonding course may be necessary.



© ift Rosenheim
Prüfbericht Nr.19-004132-PR01
(PB1-E03-020310-de-02)
• CONTEGA SOLIDO IQ
nach MO-01/1:2007-01, Abs. 5.4
01.07.2020

Tested for hazardous
substances according to



*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)



The information provided here is based on practical experience and the current state of knowledge. We reserve the right to make changes to the recommended designs and processing or to make alterations due to technical developments and associated improvements in the quality of our products. We would be happy to inform you of the current technical state of the art at the time you use our products.

Further information about the application and construction can be found in the pro clima planning documentation. For queries please call the pro clima technical hotline on +49 (0)6202 278245.

MOLL
bauökologische Produkte GmbH
Rheintalstraße 35 - 43
D-68723 Schwetzingen
Fon: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

